

Smartphone

Smart-Ex® 03

SMART-EX03-DZ1*

- Global certificates a common hardware platform
- Android[™] 13 operating system
- Wireless connections such as 5G NR, WWAN, Wi-Fi and Bluetooth®
- Android[™] Enterprise Recommended verified device
- GPS
- NFC technology for wireless applications
- Service contract
- Programmable hardware buttons
- Special buttons for lone worker protection (LWP) applications
- PTCRB and GCF certified
- Dual SIM (eSIM + nano-SIM)
- Google ARCore ready

Smart-Ex 03 DZ1 (DIV 1 and Zone 1/21), Android™, with Camera (optional), 128 GB















Technical Data

Qualcomm® Snapdragon QCM6490 and SDR753 platform Full 3GPP Rel 15 support
8 GByte
Version without camera available.
5 MP
13 MP with LED flash and phase detection autofocus optimized for ECOM scanning solutions
1080p, 720p, 480p (main camera)
128 GByte ¹
Biometric, Accelerometer, Gyrometer, Magnetometer, Barometer, Proximity, Ambient light
Can be operated while wearing gloves Extreme shock and scratch resistant Gorilla® glass
Capacitive multitouch
15.24 cm / 6 inch
1080 x 2160 pixels
Programmable push-to-talk, alarm and multifunction button Power button with fingerprint sensor Volume up/down
Li-lon battery , 4400 mAh
Charging via USB Type C + robust charging pads for charging in docking station (accessory) 3.5 mm audio interface, supporting legacy and standard 3.5mm audio accessories and updated PTT accessories through new, specific audio interface
GSM: 800 / 850 / 900 / 1800 / 1900 MHz
WCDMA: B1, B2, B4, B5, B8 (850 / 900 / 1700 / 1900 / 2100 MHz)



Technical Data	
4G	LTE: B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29, B30, B34, B38, B39, B40, B41, B42, B43, B48, B53, B66, B71
5G	NR: n1, n2, n3, n5, n7, n8, n12, n13, n14, n18, n20, n25, n28, n30, n38, n40, n41, n48 n66, n71, n77, n78, n79
WLAN	6E ready, 802.11a/b/g/n/ac/ax/e/k/r/v, support for Enterprise deployments
Bluetooth	5.2 with Low Energy support
GPS sensor	GPS, GLONASS, Galileo, QZSS, BeiDou
NFC	yes
SIM card	Dual SIM (eSIM + nano-SIM)
Software	
Operating system	Android™ 13 Android™ Enterprise Recommended verified device
SMS/MMS	yes
Ambient conditions	
Ambient temperature	-20 60 °C (-4 140 °F)
Mechanical specifications	
Degree of protection	IP68, MIL-STD-810H
Mass	400 g
Dimensions	
WxHxD	84 mm x 172 mm x 18 mm / 25 mm
Data for application in connection with haza	rdous areas
ATEX approval	
ATEX certificate	EPS 23 ATEX 1 094 X
ATEX marking	 ☑ II 2G Ex ia IIC T4 Gb ☑ II 2D Ex ia IIIC T135 °C Db Ta = -20 °C to +60 °C
International approvals	
IECEx approval	
IECEx certificate	IECEx EPS 23.0021X
IECEx marking	Ex ia IIC T4 Gb Ex ia IIIC T135 °C Db Ta = -20 °C to +60 °C
NEC/CEC approval	
NEC/CEC certificate	E115956_PRJ-17072
NEC/CEC marking	U.S. and Canada Class I Division 2, Groups A, B, C, D T4 Class II Division 2 Group FG T4
	U.S. Class I Zone 2 AEx ic IIC T4 Gc Zone 22 AEx ic IIIC T135°C Dc
	Canada Ex ic IIC T4 Gc Ex ic IIIC T135°C Dc
Further approvals	Wi-Fi CERTIFIED™ Google ARCore ready PTCRB GCF
General information	
Note	Android is a trademark of Google LLC. 1 no SD Card memory extension
Scope of delivery	Smart-Ex® 03 Li-lon battery Charger USB cable Screwdriver

Accessories

Accessories for this product can be found on the internet at www.pepperl-fuchs.com.

